

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **183630**
Product name: **SPRAY IGIENIZZANTE/DEO AMB.300**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Malizia Deo Spray Igienizzante**

1.3. Details of the supplier of the safety data sheet

Name: **MIRATO S.p.A.**
Full address: **Strada Provinciale Est Sesia**
District and Country: **28064 Landiona (NO) Italia**
Tel.: **+39 0321 827711**
Fax: **+39 0321 828273**

e-mail address of the competent person responsible for the Safety Data Sheet: **info@mirato.it**

1.4. Emergency telephone number

For urgent inquiries refer to: **+39 0321 827711**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: **Danger**

Hazard statements:

H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH208	Contains: α -HEXYLCINNAMALDEHYDE (R)-P-MENTHA-1,8-DIENE

**SECTION 2. Hazards identification ... / >>**

May produce an allergic reaction.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P211	Do not spray on an open flame or other ignition source.
P102	Keep out of reach of children.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.

Contains: PROPAN-2-OL

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)	
PROPAN-2-OL			
CAS	67-63-0	30 ≤ x < 50	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC	200-661-7		
INDEX	603-117-00-0		
BUTANO			
CAS	106-97-8	20 ≤ x < 31	Flam. Gas 1A H220
EC	203-448-7		
INDEX			
ISOBUTANO			
CAS	75-28-5	9 ≤ x < 20	Flam. Gas 1A H220
EC	200-857-2		
INDEX			
PROPANE			
CAS	74-98-6	9 ≤ x < 20	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC	200-827-9		
INDEX	601-003-00-5		
CETYL TRIMETHYL AMMONIUM BROMIDE			
CAS	57-09-0	0 ≤ x < 0,1	Acute Tox. 4 H302, STOT RE 2 H373, Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Acute 1 H400 M=10, Aquatic Chronic 1 H410 M=1
EC	200-311-3		
INDEX			
α-HEXYLCINNAMALDEHYDE			
CAS	101-86-0	0 ≤ x < 0,1	Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411
EC	202-983-3		
INDEX			
Reg. no.	01-2119533092-50-0000		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.
Percentage of propellants: 40,05 %

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SECTION 4. First aid measures ... / >>**

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.
INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

CETYL TRIMETHYL AMMONIUM BROMIDE

Nitric oxides and hydrobromic acid may develop.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

**SECTION 7. Handling and storage ... / >>****7.2. Conditions for safe storage, including any incompatibilities**

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

GBR United Kingdom EH40/2005 Workplace exposure limits (Third edition,published 2018)
TLV-ACGIH ACGIH 2019

PROPAN-2-OL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
WEL	GBR	999	400	1250	500
TLV-ACGIH		492	200	983	400

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

TLV of solvent mixture: 492 mg/m3

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	aerosol	
Colour	colourless	
Odour	characteristic	
Odour threshold	Not determined	
pH	Not applicable	
Melting point / freezing point	Not determined	
Initial boiling point	Not applicable	
Boiling range	Not available	

**SECTION 9. Physical and chemical properties** ... / >>

Flash point	Not applicable
Evaporation Rate	Not determined
Flammability of solids and gases	non determinato
Lower inflammability limit	Not determined
Upper inflammability limit	Not determined
Lower explosive limit	Not determined
Upper explosive limit	Not determined
Vapour pressure	Not available
Vapour density	Not determined
Relative density	0,69
Solubility	Non determinato
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature	Not determined
Decomposition temperature	Not determined
Viscosity	Not applicable
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Total solids (250°C / 482°F)	0,37 %		
VOC (Directive 2010/75/EC) :	67,30 %	- 466,09	g/litre
VOC (volatile carbon) :	46,52 %	- 322,17	g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

CETYL TRIMETHYL AMMONIUM BROMIDE

Decomposes at 250°C/482°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

10.6. Hazardous decomposition products

CETYL TRIMETHYL AMMONIUM BROMIDE

May develop: ammonia, nitric oxide, hydrobromic acid, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

**SECTION 11. Toxicological information ... / >>**

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:	Not classified (no significant component)
LD50 (Oral) of the mixture:	Not classified (no significant component)
LD50 (Dermal) of the mixture:	Not classified (no significant component)

PROPAN-2-OL	
LD50 (Oral)	4710 mg/kg Rat
LD50 (Dermal)	12800 mg/kg Rat
LC50 (Inhalation)	72,6 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

α -HEXYLCINNAMALDEHYDE
(R)-P-MENTHA-1,8-DIENE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

**SECTION 12. Ecological information** ... / >>

CETYL TRIMETHYL AMMONIUM BROMIDE	
LC50 - for Fish	0,6 mg/l/96h Danio rerio
EC50 - for Crustacea	0,24 mg/l/48h Echinogammarus tibaldi (Amphipod)
EC50 - for Algae / Aquatic Plants	0,025 mg/l/72h Microcystis
Chronic NOEC for Algae / Aquatic Plants	0,0011 mg/l

12.2. Persistence and degradability

CETYL TRIMETHYL AMMONIUM BROMIDE	
Solubility in water	55000 mg/l
Rapidly degradable	
PROPANE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	
PROPAN-2-OL	
Rapidly degradable	

12.3. Bioaccumulative potential

CETYL TRIMETHYL AMMONIUM BROMIDE	
Partition coefficient: n-octanol/water	3,18
PROPANE	
Partition coefficient: n-octanol/water	1,09
PROPAN-2-OL	
Partition coefficient: n-octanol/water	0,05

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Waste transportation may be subject to ADR restrictions.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number**

ADR / RID, IMDG, IATA: 1950

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

SECTION 14. Transport information ... / >>

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1



IMDG: Class: 2 Label: 2.1



IATA: Class: 2 Label: 2.1



14.4. Packing group

ADR / RID, IMDG, IATA: -

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special Provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**SECTION 15. Regulatory information ... / >>****15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Flam. Liq. 2	Flammable liquid, category 2
Press. Gas (Liq.)	Liquefied gas
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may burst if heated.
H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds



SECTION 16. Other information ... / >>

- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.